

COLLECTION	DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
		182x1220	MICRO BEVEL	STANDART	 WARRANTY (Year)
		PACKAGE(m <sup>2</sup> )	PALETTE(m <sup>2</sup> )	CONTAINER(20')	
		11 X  =2.443 m <sup>2</sup> =19.60 Kg	65 X  =158.795 m <sup>2</sup> =1.274.00 Kg	20 X  =3.175.90 m <sup>2</sup> =25.480.00 Kg	
		150x610	MICRO BEVEL	STANDART	 WARRANTY (Year)
		PACKAGE(m <sup>2</sup> )	PALETTE(m <sup>2</sup> )	CONTAINER(20')	
		20 X  =1.830 m <sup>2</sup> =14.70 Kg	84 X  =153.720 m <sup>2</sup> =1.234.80 Kg	20 X  =3.074.40 m <sup>2</sup> =24.696.00 Kg	

## Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	NO
	Thickness in Total	ISO24337	4mm
	Thickness of wear layers	EN429	0.3mm
	Weight in total	EN ISO 23997	8,0 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 <sup>0</sup> C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)



ISO 9001:2015  
ISO 14001:2015



COLLECTION	DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
		228X1220	MICRO BEVEL	STANDART	 WARRANTY (Year)
		PACKAGE(m <sup>2</sup> ) 9 X  =2,503 m <sup>2</sup> =20.20 Kg	PALETTE(m <sup>2</sup> ) 65 X  =160.220 m <sup>2</sup> =1,292.80 Kg	CONTAINER(20') 20 X  =3,204.40 m <sup>2</sup> =25,856.00 Kg	
		150x750	MICRO BEVEL	STANDART	 WARRANTY (Year)
		PACKAGE(m <sup>2</sup> ) 16 X  =1,800 m <sup>2</sup> =14.40 Kg	PALETTE(m <sup>2</sup> ) 77 X  =138.600 m <sup>2</sup> =1,108.80 Kg	CONTAINER(20') 22 X  =3,049.20 m <sup>2</sup> =24,393.60 Kg	

## Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	1mm
	Thickness in Total	ISO24337	5mm
	Thickness of wear layers	EN429	0.3mm
	Weight in total	EN ISO 23997	8,0 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 <sup>0</sup> C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)



ISO 9001:2015

ISO 14001:2015



COLLECTION	DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 DOOR PREMIUM 1 PLANK		228X1220	MICRO BEVEL	EIR	 WARRANTY (Year)
		PACKAGE(m <sup>2</sup> )	PALETTE(m <sup>2</sup> )	CONTAINER(20')	15
		9 X =2.503 m <sup>2</sup> =20.20 Kg	64 X =160.220 m <sup>2</sup> =1.292.80 Kg	20 X =3.204.40 m <sup>2</sup> =25.856.00 Kg	
 DOOR PREMIUM 1 HERRINGBONE		150x610	MICRO BEVEL	EIR	 WARRANTY (Year)
		PACKAGE(m <sup>2</sup> )	PALETTE(m <sup>2</sup> )	CONTAINER(20')	15
		16 X =1.460 m <sup>2</sup> =11.71 Kg	108 X =158.110 m <sup>2</sup> =1.264.90 Kg	20 X =3.162.24 m <sup>2</sup> =25.297.92 Kg	

## Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	1mm
	Thickness in Total	ISO24337	5mm
	Thickness of wear layers	EN429	0.5mm
	Weight in total	EN ISO 23997	8,0 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 <sup>0</sup> C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)



ISO 9001:2015  
ISO 14001:2015



COLLECTION	DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
		228X1220	MICRO BEVEL	EIR	
		PACKAGE(m <sup>2</sup> )	PALETTE(m <sup>2</sup> )	CONTAINER(20')	WARRANTY(Year)
		7 X =1,950 m <sup>2</sup> =19.47 Kg	64 X =124.620 m <sup>2</sup> =1,246.16 Kg	20 X =2,492.31 m <sup>2</sup> =24,923.14 Kg	15
		150x750	MICRO BEVEL	EIR	
		PACKAGE(m <sup>2</sup> )	PALETTE(m <sup>2</sup> )	CONTAINER(20')	WARRANTY(Year)
		14 X =1.580 m <sup>2</sup> =15.75 Kg	70 X =110.250 m <sup>2</sup> =1,102.50 Kg	22 X =2,425.50 m <sup>2</sup> =24,255.00 Kg	15





## Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	1mm
	Thickness in Total	ISO24337	6mm
	Thickness of wear layers	EN429	0.5mm
	Weight in total	EN ISO 23997	9,5 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 <sup>0</sup> C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)




















ISO 9001:2015  
ISO 14001:2015



COLLECTION	DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
<b>STONE</b>		305X610 PACKAGE(m <sup>2</sup> ) 11 X  =2.047 m <sup>2</sup> =16.37 Kg	MICRO BEVEL PALETTE(m <sup>2</sup> ) 78 X  =159.630 m <sup>2</sup> =1.277.05 Kg	STANDART CONTAINER(20') 20 X  =3.192.62 m <sup>2</sup> =25.540.94 Kg	<b>UNICLIC</b> <sup>®</sup> PATENTED TECHNOLOGY WARRANTY(Year) <b>15</b>

## Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	NO
	Thickness in Total	ISO24337	4mm
	Thickness of wear layers	EN429	0.3mm
	Weight in total	EN ISO 23997	8,0 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 <sup>0</sup> C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)



ISO 9001:2015

ISO 14001:2015



COLLECTION	DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
		305X1220 PACKAGE(m <sup>2</sup> ) 6 X =2,230 m <sup>2</sup> =17.86 Kg	MICRO BEVEL PALETTE(m <sup>2</sup> ) 72 X =160,750 m <sup>2</sup> =1,285.98 Kg	STANDART CONTAINER(20') 20 X =3,214.94 m <sup>2</sup> =25,719.55 Kg	 WARRANTY(Year) 15

## Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	1mm
	Thickness in Total	ISO24337	5mm
	Thickness of wear layers	EN429	0.3mm
	Weight in total	EN ISO 23997	8,0 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 <sup>0</sup> C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)



ISO 9001:2015

ISO 14001:2015

